


# Material Safety Data Sheet

WHMIS	Protective Clothing 	TDG Road / Rail
-------	--	-----------------

## Section 1. Product Identification and Uses

Product Name	80828 Teflon Coat	CI#	Not available.
Synonyms	Not available.	DBL	Not available.
Chemical Name	Not applicable.	CAS #	Not applicable.
Chemical Formula	Chemical mixture.	Code	1453-01-001
Chemical Family	Various Hydrocarbons.	Molecular Weight	Not applicable.
Supplier	Dixie Packing & Seal Co. 1900 Elm Tree Drive, Nashville, Tennessee, U.S.A. 37210 PHONE: (615) 883-5592	Manufacturer	Manufactured for: Dixie Packing & Seal Co.
Material Uses	Teflon Coat provides a slippery, nongreasy, non-staining, water resistant coating on nonporous surfaces.		


## Section 2. Hazardous Ingredients

Name	CAS #	% by Weight	LC <sub>50</sub> /LD <sub>50</sub>
1) N-hexane	110-54-3	10-30	ORAL (LD50): Acute: 32400 mg/kg [Rat].
2) Isopropanol	67-63-0	5-15	ORAL (LD50): Acute: 5045 mg/kg [Rat].
3) Solvent Naphtha	64742-89-8	5-15	ORAL (LD50): Acute: >25000 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit].
4) Polymer	65530-85-0	1-5	Not available.
5) Propane	74-98-6	5-10	Not available.
6) Iso-Butane	75-28-5	30-60	Not available.

## Section 3. Physical Data

Physical State and Appearance	Liquid (Aerosol Concentrate).	Odor	Characteristic.
pH (1% Soln/Water)	Not available.	Taste	Not available.
Odor Threshold	Not available.	Color	Clear
Volatility	Not available.		
Evaporation Rate	Not available.		
Melting Point	Not available.		
Boiling Point	The lowest known value is 68.95°C (156.1°F) (N-hexane).		
Density	0.743 @20°C (Water = 1)		
Vapor Density	The highest known value is 2.97 (Air = 1) (N-hexane).		
Vapor Pressure	The highest known value is 16.5 kPa (@ 20°C) (N-hexane).		
LogK <sub>ow</sub>	Not available.		
Toxicity (Surface Active Agent)	Not available.		
Critical Temperature	Not available.		
Instability Temperature	Not available.		
Conditions of Instability	Not available.		
Dispersion Properties	See solubility in water.		
Solubility	Insoluble in water.		

Continued on Next Page

WHMIS	Protective Clothing	TDG Road / Rail
Not applicable.		CONSUMER COMMODITY, ORM-D


### Section 4. Fire and Explosion Data

The Product is:	Extremely Flammable Aerosol
Auto-ignition Temperature	The lowest known value is 223°C (433.4°F) (N-hexane).
Products of Combustion	These products are carbon monoxide, carbon dioxide and other irritating gases.
Flash Points	The lowest known value is CLOSED CUP: 2.16°C (35.9°F). (TAG). (N-hexane)
Flammable Limits	The greatest known range is LOWER: 0.6% UPPER: 7% (N-hexane)
Extinguishing Media	SMALL FIRE: Use DRY chemicals, carbon dioxide or foam. LARGE FIRE: Use foam or water fog. Cool containing vessels with water spray in order to prevent pressure build-up, autoignition or explosion. Avoid spreading burning liquid with water used to cool containers. Self-contained respiratory protection should be provided for firefighters.
Flammability	The flammability of an aerosol by WHMIS definition is determined by its flame-extension or its flashback. The flame-extension of this product is greater than 45 cm. FIRE CODE: Level 3 Aerosol (as per NFPA 30B). Do not use in the presence of open flame or spark. Do not place in hot water or near radiators, stoves or other sources of heat.
Risks of Explosion	Risk of explosion of the product in presence of mechanical impact: Do not subject aerosol cans to impact. Risk of explosion of the product in the presence of static discharge: Aerosol spray may be sensitive to static discharge due to flammable concentrate and flammable propellant. Vapours of this product may form a flammable/explosive mixture with air in enclosed areas when vapours present are between the lower (0.6%) and upper (7.0%) flammable limits and come into contact with open flames, sparks or static discharge. Do NOT expose aerosol containers to open flames, heat or ignition sources. Container may explode if heated.

### Section 5. Reactivity

Stability	The product is stable.
Hazardous Decomposition Products	These products are carbon monoxide, carbon dioxide and other irritating gases.
Degradability	Not available.
Products of Degradation	Not available. Not available.
Corrosivity	No specific information is available in our data base regarding the corrosivity of this product in presence of various materials.
Reactivity	Avoid contact with strong oxidizing agents, strong acids and strong alkalis. Keep away from heat, sparks, open flame and all possible ignition sources.
Instability Temperature	Not available.
Conditions of Instability	Not available.

Continued on Next Page

WHMIS	Protective Clothing	TDC Read / Fall
Not applicable.		
		CONSUMER COMMODITY, ORM-D

## Section 6. Toxicological Properties


Routes of Entry	Inhalation, Ingestion.
TLV	<p><b>N-hexane</b> TWA: 50 CEIL: 125 TWA: 360 CEIL: 450</p> <p><b>Isopropanol</b> TWA: 400 from ACGIH (TLV) [United States] [1986]</p> <p><b>Propane</b> Simple asphyxiant.</p> <p>Consult local authorities for acceptable exposure limits.</p>
Toxicity to Animals	<p>Acute oral toxicity (LD50): 32400 mg/kg [Rat]. (N-hexane). Acute oral toxicity (LD50): 5045 mg/kg [Rat]. (Isopropanol). Acute toxicity of the vapor (LC50): &gt;5000 ppm (Rat) (Isopropanol). Acute toxicity of the gas (LC50): 142500 ppm 4 hour(s) [Rat]. (Iso-Butane).</p>
Chronic Effects on Humans	Prolonged or repeated skin contact may lead to dermatitis.
Acute Effects on Humans	<p><b>EYE CONTACT:</b> May cause irritation, redness and tearing.</p> <p><b>SKIN CONTACT:</b> May cause irritation, defatting, drying and cracking of skin.</p> <p><b>INHALATION:</b> Vapours may be irritating to nose, throat and respiratory tract. Excessive inhalation of vapours may cause Central Nervous System effects including dizziness, weakness, fatigue, nausea, headache and possible unconsciousness.</p> <p><b>INGESTION:</b> May cause gastrointestinal irritation, nausea, vomiting and diarrhea. Aspiration of material into the lungs may cause chemical pneumonitis, which can be fatal. Can be fatal if inhaled or ingested. This product may irritate eyes and skin upon contact.</p>
Synergistic Products (Toxicologically)	Not available.
Irritation/Corrosivity	See acute effects on humans.
Sensitization	Not available.
Carcinogenic Effects	Not available.
Toxic Effects on Reproduction	DEVELOPMENTAL TOXICITY: Not available.
Teratogenic Effects	TERATOGENIC EFFECTS: Not available.
Mutagenic Effects	Not available.

## Section 7. Preventive Measures

Small Spill and Leak	Ventilate area and eliminate all sources of ignition. Keep away from heat. Absorb with an inert DRY material and place in an appropriate waste disposal container.
Personal Protective Equipment	Recommend safety glasses and chemical resistant gloves.
Large Spill and Leak	Not applicable for aerosol containers.
Protective Clothing	Not applicable for aerosol containers.
Engineering Controls	Use under well-ventilated conditions.



Continued on Next Page

<b>80828 Teflon Coat</b>		<b>Page Number: 4</b>
WHMIS	Protective Clothing	TDG Road / Rail
		
Not applicable.		CONSUMER COMMODITY, ORM-D

<b>Precautions</b>	Contents under pressure. Container may explode if heated. Direct inhalation of spray may be harmful. Keep out of reach of children.
<b>Storage</b>	Store in a cool, dry place. Do not place in hot water or near radiators, stoves or other sources of heat. Do not puncture or incinerate container or store at temperatures over 50°C or in direct sunlight.
<b>Handling</b>	Do not use in the presence of open flame, sparks or ignition sources. Keep away from heat. Avoid breathing vapours or spray mists. If ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes. After handling, always wash hands thoroughly with soap and water.
<b>Waste Disposal</b>	Recycle to process, if possible. Consult your local or regional authorities. Do not dispose in sewers. When container is empty, press button to release all pressure, then dispose of in garbage can.
<b>Special Shipping Information</b>	Not available.

<b>Section 8. First Aid</b>	
<b>Eye Contact</b>	Flush eyes with plenty of running water for at least 15 minutes, lifting upper and lower lids, occasionally. Get medical attention.
<b>Skin Contact</b>	Wash thoroughly with soap and water. If irritation persists, get medical attention. Remove contaminated clothing and wash before reuse.
<b>Hazardous Skin Contact</b>	No additional information.
<b>Slight Inhalation</b>	Remove affected person to fresh air. If breathing is difficult, administer oxygen. If breathing stops give artificial respiration. Get medical attention.
<b>Hazardous Inhalation</b>	No additional information.
<b>Slight Ingestion</b>	If swallowed, call physician or poison control centre immediately. DO NOT induce vomiting. Rinse mouth with water. Aspiration of material into lungs due to vomiting may cause chemical pneumonitis which can be fatal.
<b>Hazardous Ingestion</b>	No additional information.

<b>Section 9. MSDS Preparation</b>	
<b>References</b>	Not available.
No additional remark.	
Validated by Regulatory Affairs Dept. on 10/7/2002.	Verified by Regulatory Affairs Dept. Printed 10/8/2002.

**Emergency Phone: (905) 677-1948**


Responsible Name/  
Telephone No.

<b>Classification</b>	
TDG Road / Rail	CONSUMER COMMODITY, ORM-D
	Not applicable.

**Continued on Next Page**

80828 Teflon Coat

Page Number: 5

WHMIS	Protective Clothing	TDG Road / Rail
		
Not applicable.		CONSUMER COMMODITY, ORM-D

WHMIS Not applicable.	
-----------------------	--

*To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.*